

**BMP-3**

**ROF**

**Notes**



30mm Autocannon	4
100mm Gun/Launcher	2
PTK 7.62mm Coax	4



Conventional Fire					
Round	0-200	250-350	400-1100	1150-1800	1850-2250
PTK 7.62mm	12	8	4		

M or S	30mm HEAT	0-500	120	550-1000	110	1050-1500	90	1550-2000	70	2050-2250	50	2300-3000	30
Moving	100mm HEAT	0-200	150	250-400	140	450-600	130	650-800	120	850-1500	110	1550-2500	100
Stationary	100mm HEAT	0-200	150	250-450	140	500-700	130	750-900	120	950-1750	110	1800-2700	100

M or S	AT-10 Stabber	0-100	101-150	160	151-200	160	201-250	160	251-300	160	301-3500	160

**BMP-3**

-4	Target Hardness	750	Open Movement (Meters)
2	CH	1100	Road Movement (Meters)



Defilade	40	70	90	17	40	60	23	10	52	30	10	30	33	5	13	40	3	
Overhead	10	100	90	30	100	80	56	90	70	67	70	60	80	30	32	90	20	10
Oblique/Side	20	100	90	30	90	80	46	70	70	60	40	60	80	20	33	90	10	11
Front/Rear	40	100	90	30	90	80	40	70	69	60	30	60	70	10	31	90	10	