

**T-72 Reactive Armor**

ROF

Notes



125mm Gun

5

12.7 DShK

4



Conventional Fire						
Round	0-200	250-350	400-1100	1150-1800	1850-2250	
HE	24	18	16	8	3	
12.7 DShk	7	5	4	3	1	

Moving	APFSDS	0-500	200	550-800	200	850-1000	180	1050-1750	180	1800-2700	140	2750-3400	120
	HEAT	0-250	190	300-400	190	450-600	190	650-800	190	850-1500	190	1550-2500	190
Stationary	APFSDS	0-500	200	550-1000	200	1050-1500	180	1550-2000	180	2050-2750	140	2800-3500	120
	HEAT	0-250	190	300-500	190	550-750	190	800-1000	190	1050-2000	190	2050-3000	190

**T-72 Reactive Armor**

-6 Target Hardness

650

Open Movement (Meters)

1 CH

1000

Road Movement (Meters)



Defilade	150	100	90	18	70	60	26	40	52	33	10	35	35	10	15	50	5	4	
Overhead	40	100	90	30	100	80	58	90	71	68	70	61	80	30	33	90	20	11	
Oblique/Side	90	50	100	90	30	90	80	48	70	70	60	40	61	80	20	34	90	10	11
Front/Rear	150	40	100	90	30	90	80	40	70	69	60	30	61	70	10	32	90	5	10