

T-80

ROF

Notes



125mm Gun

5

12.7 DShK

4



		Conventional Fire											
Round		0-200		250-350		400-1100		1150-1800		1850-2250			
HE		24		18		16		8		3			
12.7 DShk		7		5		4		3		1			
Moving	APFSDS	0-500	200	550-800	200	850-1000	180	1050-1750	180	1800-2700	140	2750-3400	120
	HEAT	0-250	190	300-400	190	450-600	190	650-800	190	850-1500	190	1550-2500	190
Stationary	APFSDS	0-500	200	550-1000	200	1050-1500	180	1550-2000	180	2050-2750	140	2800-3500	120
	HEAT	0-250	190	300-500	190	550-750	190	800-1000	190	1050-2000	190	2050-3000	190

T-80

-8 Target Hardness

800

Open Movement (Meters)

1 CH

1150

Road Movement (Meters)



Defilade	180	100	90	18	70	60	26	40	52	33	10	35	35	10	15	50	5	4	
Overhead	50	100	90	30	100	80	58	90	71	68	70	61	80	30	33	90	20	11	
Oblique/Side	120	60	100	90	30	90	80	48	70	70	60	40	61	80	20	34	90	10	11
Front/Rear	180	40	100	90	30	90	80	40	70	69	60	30	61	70	10	32	90	5	10